



SM-RW

Versions of S.M. HID capacitors

Outlook (General Data) SM-RW (1.0 ~ 120.0 μ F)

Dims. in mm. Temperature = 105°C

Life term = 60,000 hours

Protected = 10,000 AFC

1.0 ~ 7.0 μ F

CAP	120~180VAC		200~240VAC		250~320VAC		330~370VAC		380~450VAC		460~500VAC		510~550VAC		560~660VAC	
μ F	D	L	D	L	D	L	D	L	D	L	D	L	D	L	D	L
1.0							25.0	40.0	25.0	40.0	25.0	40.0	30.0	40.0	30.0	40.0
1.5							25.0	40.0	25.0	40.0	30.0	40.0	30.0	40.0	30.0	52.0
2.0					25.0	40.0	25.0	40.0	30.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5
2.5					25.0	40.0	30.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0
3.0			25.0	40.0	25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	52.5	40.5	60.5
3.5			25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	52.5	35.5	61.0	40.5	60.5
4.0	25.0	40.0	25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	35.5	61.0	40.5	60.5
4.5	25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	52.5	35.5	61.0	40.5	60.5	40.5	65.0
5.0	25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	35.5	61.0	40.5	60.5	40.5	65.0
5.5	25.0	40.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	60.5	45.5	77.0
6.0	25.0	40.0	30.0	40.0	35.5	52.5	35.5	52.5	35.5	61.0	40.5	60.5	40.5	60.5	45.5	77.0
6.5	25.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0
7.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0

7.5 ~ 24.0 μ F

CAP	120~180VAC		200~240VAC		250~320VAC		330~370VAC		380~450VAC		460~500VAC		510~550VAC		560~660VAC	
μ F	D	L	D	L	D	L	D	L	D	L	D	L	D	L	D	L
7.5	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0
8.0	30.0	40.0	30.0	52.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0
9.0	30.0	40.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0
10.0	30.0	52.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0
12.0	30.0	52.0	35.5	52.5	40.5	60.5	40.5	60.5	45.5	77.0	45.5	77.0	45.5	77.0	52.0	90.0
14.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0
15.0	35.5	52.5	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0	52.0	125.0
16.0	35.5	52.5	35.5	61.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0
18.0	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0
20.0	35.5	61.0	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	90.0	60.0	125.0
22.0	35.5	61.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0
23.0	35.5	61.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0
24.0	35.5	61.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0

Versions of S.M. **HID** capacitors - ISO-9001 certified

25.0 ~ 45.0 μ F

CAP	120~180VAC		200~240VAC		250~320VAC		330~370VAC		380~450VAC		460~500VAC		510~550VAC		560~660VAC	
μ F	D	L	D	L	D	L	D	L	D	L	D	L	D	L	D	L
25.0	35.5	61.0	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0
26.0	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	90.0	52.0	125.0	MAX 25.0 μ F	
28.0	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0		
30.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0		
32.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0		
33.0	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0	60.0	125.0		
35.0	40.5	60.5	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0	60.0	125.0		
36.0	40.5	60.5	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0	60.0	125.0		
38.0	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0	MAX 36.0 μ F			
40.0	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0				
42.0	40.5	65.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0	60.0	125.0				
44.0	40.5	65.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0	60.0	125.0				
45.0	45.5	77.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0						

47.0 ~ 120.0 μ F

CAP	120~180VAC		200~240VAC		250~320VAC		330~370VAC		380~450VAC		460~500VAC		510~550VAC		560~660VAC	
μ F	D	L	D	L	D	L	D	L	D	L	D	L	D	L	D	L
47.0	45.5	77.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0	MAX 44.0 μ F					
50.0	45.5	77.0	52.0	90.0	52.0	90.0	52.0	125.0	60.0	125.0						
55.0	45.5	77.0	52.0	90.0	52.0	90.0	60.0	125.0	60.0	125.0						
60.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0	MAX 56.0 μ F							
65.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0								
70.0	45.5	77.0	52.0	90.0	52.0	125.0	60.0	125.0								
75.0	52.0	90.0	52.0	90.0	60.0	125.0	MAX 72.0 μ F									
80.0	52.0	90.0	52.0	90.0	60.0	125.0										
85.0	52.0	90.0	52.0	125.0	60.0	125.0										
90.0	52.0	90.0	52.0	125.0	60.0	125.0										
95.0	52.0	90.0	52.0	125.0	60.0	125.0										
100.0	52.0	90.0	52.0	125.0	MAX 97.0 μ F											
120.0	52.0	90.0	60.0	125.0												