



**Electronic Alliance**

## 150W Single Output (Mini-size)



### **150W Single Output (Mini-size)**

Universal AC input/ full range  
Power on indication  
Overload /Over voltage /Short Circuit Protection  
100% full load burn-in test  
One year warranty  
Size:199mm x98mm x 38mm

#### **Specifications:**

AC input voltage	88-132VAC/176-264 VAC SELECTED BY SWITCH					
Input frequency	47~63Hz					
Inrush current	40A @230VAC,full load cold start					
hold up time	25ms@230 VAC,100% of rated maximum load					
Overload protection	110%- 150%					
Over voltage protection	110%-140%					
Working temperature	-10 to 50°C					
Safety standard	UL60950-1					
EMC standard	EN55022 class B					
MTBF	10 <sup>5</sup> h at 25°C					
Withstand Voltage	I/P-O/P:3KV,I/P-FG:1.5KV,1min					
Weight	0.7Kg/pcs					
P/N	Output	Tol.	R&N	Effi.	LoadRegulation	Line Regulation
<b>ESPR-150-3.3</b>	<b>3.3V,30A</b>	3%	80mV	74%	3%	3%
<b>ESPR-150-5</b>	<b>5V,26A</b>	2%	80mV	78%	2%	2%
<b>ESPR-150-12</b>	<b>12V,12.5A</b>	1%	120mV	83%	1%	1%
<b>ESPR-150-24</b>	<b>24V,6.5A</b>	1%	120mV	86%	1%	1%
<b>ESPR-150-48</b>	<b>48V,3.3A</b>	1%	200mV	87%	1%	1%